

Printing date 26.05.2016 Revision: 26.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: DAMMAR VARNISH MATT 082

• *Article number*: 2400.0082

· 1.2 Relevant identified uses of the substance or mixture picturevarnish

· 1.3 Manufacturer/Supplier:

Royal Talens P.O.Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

· Further information obtainable from:

Regulatory Affairs safety@talens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Bermingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labelling: Turpentine, oil

(Contd. on page 2)



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour. H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to hazardous waste collection point.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 8006-64-2	Turpentine, oil	50-100%
EINECS: 232-350-7	© Flam. Liq. 3, H226; © Asp. Tox. 1, H304; © Aquatic Chronic 2, H411; © Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
	propan-2-ol	1-5%
	🚸 Flam. Liq. 2, H225; ᡧ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25		

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; call for medical help immediately.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

GB



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients	with limit	t values the	at roamiro	monitoring	at the	worknlace.
ingreatents	will illill	i vuiues iiu	u regune	monuom	ui iiie	workplace.

8006-64-2 Turpentine, oil

WEL Short-term value: 850 mg/m³, 150 ppm Long-term value: 566 mg/m³, 100 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Only during spraying without adequate removal by suction.

· Protection of hands:



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

· Material of gloves Nitrile rubber, NBR

(Contd. on page 4)



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 3)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses if risk of splashes.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined. *Boiling point/Boiling range:* > 78 °C

· Flash point: 19 °C

· Ignition temperature: 220 °C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

 Lower:
 0.8 Vol %

 Upper:
 6.0 Vol %

· Vapour pressure at 20 °C: 5.4 hPa

• **Density at 20 °C:** 0.92 g/cm³

· Solubility in / Miscibility with water: Not miscible or difficult to mix.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:				
8006-64-2 Turpentine, oil				
Oral	LD50	> 5000 mg/kg (rat)		
Inhalative	LC50/4 h	> 10 mg/l (rat)		

(Contd. on page 5)



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 4)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

 $\cdot \textit{ Serious eye damage/irritation }$

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information				
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263			
· 14.2 UN proper shipping name				
$\cdot ADR$	1263 PAINT RELATED MATERIAL,			
	ENVIRONMENTALLY HAZARDOUS			
· IMDG	PAINT RELATED MATERIAL (TURPENTINE), MARINE			
	POLLUTANT			
· IATA	Paint related material			

(Contd. on page 6)



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 5) · 14.3 Transport hazard class(es) · ADR, IMDG · Class 3 Flammable liquids. · Label \cdot IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group II· ADR, IMDG, IATA · 14.5 Environmental hazards: Product contains environmentally hazardous substances: Turpentine, oil · Marine pollutant: Yes Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): · 14.6 Special precautions for user Warning: Flammable liquids. · Danger code (Kemler): F-E,S-E· EMS Number: · Stowage Category · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: $\cdot ADR$ · Limited quantities (LQ) 5LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E \cdot *IMDG* · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1263 PAINT RELATED MATERIAL, 3, II, · UN ''Model Regulation'':

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

ENVIRONMENTALLY HAZARDOUS

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

(Contd. on page 7)



Printing date 26.05.2016 Revision: 26.05.2016

(Contd. of page 6)

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

GB